

# Service Multi-Deck Narrow Candy Merchandiser w/ Fixed Glass

**CDC REMOTE - 48", 59", 77", 96", 120", EW-90, & IW-90**

## Electrical Data

Model		Fans per Case	Box Fans		Re-Heaters		Drain Heaters		Optional Defrost Heaters	
			120 Volts		120 Volts		120 Volts		208 Volts	
			Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
CDC	48"	2	0.8	96	1.375	165	---	---	---	---
	59"	2	0.8	96	1.67	200.4	---	---	---	---
	77"	4	1.6	192	2	240	---	---	---	---
	96"	4	1.6	192	2.5	300	---	---	---	---
	EW-90	2	0.8	96	1.375	165	---	---	---	---
	IW-90	2	0.8	96	1.375	165	---	---	---	---

## Lighting Data

Model		Lights per Row	Light Length (ft)	Fluorescent Lighting (Per Light Row)		Clearvoyant LED Lighting (Per Light Row)			
				120 Volts		Standard Power (Cornice or Shelf)		High Power (Cornice)	
				120 Volts		120 Volts		120 Volts	
				Amps	Watts	Amps	Watts	Amps	Watts
CDC	48"	1	4	0.27	32.4	0.12	14.4	0.20	24
	59"	1	5	0.32	38.4	0.1475	17.7	0.25	29.5
	77"	2	3	0.34	40.8	0.1925	23.1	0.32	38.5
	96"	2	4	0.47	56.4	0.24	28.8	0.40	48
	EW-90	1	3	0.21	25.2	0.09	10.8	0.15	18
	IW-90	1	2	0.15	18	0.06	7.2	0.1	12

## Guidelines & Control Settings (DX)

Model	Conventional <sup>2</sup> BTUH/ft	Parallel <sup>3</sup> BTUH/ft	Superheat Set Point @ Bulb (°F)	Evaporator (°F)	Discharge Air (°F)	Discharge Air <sup>4</sup> Velocity (FPM)
CDC	490	450	10	45	50	200

## Defrost Controls

Model	Defrosts per Day	Run-Off Time (min)	Electric Defrost		Timed-Off Defrost		Hot Gas Defrost	
			Fail-Safe (min)	Termination Temp (°F)	Fail-Safe (min)	Termination Temp (°F)	Fail-Safe (min)	Termination Temp (°F)
CDC	---	---	---	---	---	---	---	---

1 NOTE: "--" indicates data not applicable.

2,3 Listed BTUH indicates unlighted shelves. Add the following for lighted shelves:

- 4' Fluorescent: 80 BTUH
- 3' Fluorescent: 60 BTUH
- 4' Shelf LED: 36 BTUH
- 4' Canopy LED: 72 BTUH
- 3' Shelf LED: 27 BTUH
- 3' Hi-Output LED: 54 BTUH

4 Average discharge air velocity at peak of defrost.

Engineered for stores with ambient conditions not to exceed 75° and 55% relative humidity.

Due to engineering improvements specifications may change without notice.

All measurements are taken per ASHRAE - 72 - 2005 specifications.

Numbers are based on standard case sizes. Consult engineering.



