

SOLOCHILL[®]

MICRO DISTRIBUTED

AVAILABLE CASES

	Display Case		Lengths						2	3	4	5	6
			4'	6'	8'	10'	12'						
Reach-In Low-Temp	ORZQA	VA						✓	✓	✓	✓	✓	
	ORZHQA	VA						✓	✓	✓	✓	✓	
	ONRZQA	VA						✓	✓	✓	✓	✓	
	ONRZHQA	VA						✓	✓	✓	✓	✓	
	VNRZQA	VA						✓	✓	✓	✓		
	VNRZHQA	VA						✓	✓	✓	✓		
Reach-In Medium-Temp	ORBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	
	ORBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	
	ORBR				✓		✓						
	ONRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	
	ONRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓	✓	
	VRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓		
	VRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓		
	VNRBQA	VA	✓	✓	✓		✓	✓	✓	✓	✓		
VNRBHQA	VA	✓	✓	✓		✓	✓	✓	✓	✓			
Utility	DLPC	IA	✓	✓	✓	✓	✓						
	KFD (Slave/Secondday Only) (No master)	IA	✓	✓	✓	✓	✓						
	NFD	IA	✓	✓	✓	✓							
	NFT	IA	✓	✓	✓	✓							
	NFO	IA	✓	✓	✓	✓							
	O2MZD	VA			✓								
	O3UMQA	VA			✓		✓						
	O4UMQA	VA			✓		✓						
	O25UMQA	VA			✓		✓						
	O35UMQA	VA			✓		✓						
	O325UMQA	VA			✓		✓						
	ON3UMQA	VA			✓		✓						
	ON4UMQA	VA			✓		✓						
	O5UMQA	VA			✓		✓						
	ON5UMQA	VA			✓		✓						
	ON35UMQA	VA			✓		✓						
	O3UDQA	VA			✓		✓						
	OMQA	VA			✓		✓						
	QCD	IA	✓	✓	✓		✓						
	PC-G-R	IA	✓	✓	✓	✓	✓						
	Multi-Deck	BLF-SR	IA	✓	✓	✓							
		DLPF	IA	✓	✓	✓	✓	✓					
		FT	IA	✓	✓	✓	✓	✓					
		O5MQA	VA	✓	✓	✓		✓					
O5DR		VA			✓								
O5MHQA		VA	✓	✓	✓		✓						
O5DMQA		VA	✓	✓	✓	✓	✓						
O5DMHQA		VA	✓	✓	✓	✓	✓						
ON5DMXQA		VA	✓	✓	✓	✓	✓						
ON5DMHXQA		VA	✓	✓	✓		✓						
ON5MHXQA		VA	✓	✓	✓		✓						
OHPQA		VA	✓	✓	✓		✓						
OHPHQA		VA	✓	✓	✓		✓						
OHMQA		VA	✓	✓	✓		✓						
OHHMQA		VA	✓	✓	✓		✓						
6DMLHQA		VA	✓	✓	✓		✓						
6MLHQA		VA	✓		✓		✓						
6NDMLHQA		VA			✓		✓						
PF - 48", 51", 54", 72"		IA	✓	✓	✓	✓	✓						
QC		IA	✓	✓	✓	✓	✓						

	Case Model		Lengths				
			4'	6'	8'	10'	12'
Islands Low-Temp	OWIZVQA	VA	✓	✓	✓		✓
	OWEZVQA	VA		✓			
	ONIZGGQA	VA		✓	✓		✓
	OWZGGQA	VA		✓	✓	✓	✓
	OEWZQA	VA	✓				
Islands Medium-Temp	i2i (Ft length notes length of center section)	IA	✓	✓	✓	✓	✓
	PFI (Ft length notes length of center section)	IA	✓	✓	✓	✓	✓
Service	AGB	IA	✓	✓	✓		
	BLF-R	IA	✓	✓	✓		
	BMD-R	IA	✓	✓	✓	✓	✓
	BMD-RG	IA	✓	✓	✓	✓	✓
	BSD-SW	IA	✓	✓	✓	✓	✓
	GMD-R	IA	✓	✓	✓	✓	✓
	GMD-RG	IA	✓	✓	✓	✓	✓
	GMD-RGC / SSC	IA		✓	✓	✓	✓
	GSD-R	IA	✓	✓	✓	✓	✓
	SMD-R	IA	✓	✓	✓	✓	✓
	SMD-RG	IA	✓	✓	✓	✓	✓
	SSD-R	IA	✓	✓	✓	✓	✓
	SSD-R-LT	IA	✓	✓			
	SSGC	IA		✓	✓	✓	✓
	S2SGC	IA		✓	✓	✓	✓
	S2SG	IA	✓	✓	✓	✓	✓
	S2SB	IA	✓	✓	✓	✓	✓
	SSA	IA	✓	✓	✓	✓	✓
	SSAW	IA	✓	✓	✓	✓	✓
	SSA-RG	IA	✓	✓	✓	✓	✓
	SSM	IA	✓	✓	✓	✓	✓
	SSAM-RG	IA	✓	✓	✓	✓	✓
	SSAS-RG	IA	✓	✓	✓	✓	✓
	SSF	IA	✓	✓	✓	✓	✓
SSF-RG	IA	✓	✓	✓	✓	✓	
SSFM - RG	IA	✓	✓	✓	✓	✓	
SSFS - RG	IA	✓	✓	✓	✓	✓	
SGM	IA	✓	✓	✓	✓	✓	
Combo	PT	IA	✓	✓	✓	✓	✓
	PTD-R	IA	✓	✓	✓	✓	✓
	PTD-RG	IA	✓	✓	✓	✓	✓
	PTD-RGC / SSC	IA		✓	✓	✓	✓
	PTD-GSD	IA	✓	✓	✓	✓	✓
	SD-RG	IA	✓	✓	✓	✓	✓
Food Bar	SD	IA	✓	✓	✓	✓	✓
	DB	IA	✓	✓	✓	✓	✓
	BLF-CR	IA	✓	✓	✓	✓	✓
	CWC	IA	✓	✓	✓	✓	✓
	MCWC	IA	✓	✓	✓	✓	✓
	SB	IA	✓	✓	✓	✓	✓
SBI	IA	✓	✓	✓	✓	✓	

KEY: ✓ = Remote Units

This new feature simplifies the installation process by eliminating the need to run cabling between the SoloChill unit and case for EEV, fan, and defrost heater control. Only communication wires and refrigerant piping are required. The remote case will require a separate power feed.

Check with your Hillphoenix representative for detailed line-up design and engineering.

SOLOCHILL®

MICRO DISTRIBUTED

Hillphoenix
a  company

2016 Gees Mill Road / Conyers GA 30013 / Phone: 770-285-3100 / Website: hillphoenix.com