

## XTREME POWER CONVERSION P91 5KW

Online UPS



MODEL NUMBER		P91-5K
CAPACITY	Power Rating	5kVA(5KW)
INPUT	Voltage	110-300VAC
	Frequency	50/60Hz
OUTPUT	Voltage	208/220/230/240VAC (208/120V or 240/120V with optional transformer)***
	Frequency	50/60Hz ± 4Hz
	THD (full load)	< 4%
	Overload capacity	110% 10 min; 130% 1 min; >130%1 sec
	Efficiency	Up to 94% online mode or 99% ECO mode
BATTERY	Charger amps	1-4A
	Nominal/float voltage	240/273VDC
DIMENSIONS & WEIGHT	Dimensions (W x D x H)	17.2 x 23.6 x 3.5 in
	Weight	33.1 lbs.
BYPASS DISTRIBUTION MODULE	Model	XBDM-P91A (5 or 6kVA)
	Input connection	L6-30P with 6' cord
	Output connection	(2) L6-30R + (2) C19** each with breaker
ENVIRONMENT	Operating temperature	32-104°F (0-40°C)
	Audible noise	< 55dBA
	Altitude	11,500 ft above sea level
APPROVALS		UL 1778, cUL, FCC, RoHS, CE, TAA compliant

\*Depending on load level. \*\*Optional locking C20 dongles; L6-30R, L6-20R, 6-20R. \*\*\*P91 capacity derates to 90% at 208V output voltage.

BATTERY PACK DATA	
Model Number	BPXR2U240A
Dimensions	17.2 x 27.4 x 3.5 in (2U)
Weight	120 lbs.
Battery Type	(20) 12V 5AH Lead Acid

The above information is published and owned by the original equipment manufacturer, XPC Corporation. Hillphoenix has been give permission by XPC Corporation to share this information.