
GENERAL NOTES:

- "---" indicates that the feature is not an option on this case model and/or the data is not available at this time.
- · LED lights only.
- · Maximum of 5 rows of Standard Output LED lighted shelves.



SHIPPING WEIGHT		
Case	Weight	
ON5DMHX-NRG		



COMPONENT ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE



ELECTRICAL DATA

		High Effic	iency Fans
Case	Fans Per	120	Volt
Length	Case	Amps	Watts
4'	1	0.23	18.0
6'	2	0.47	35.0
8'	2	0.47	35.0
12'	3	0.70	53.0

LIGHTING DATA

		Clearvoyant v4 LED Lighting (Per Light Row)			ting
		Standard Power (Cornice or Shelf)			Power ce Only)
Case	Lights	120 Volts		120	Volts
Length	per row	Amps	Watts	Amps	Watts
4'	1	0.05	5.9	0.12	14.9
6'	2	0.08	9.4	0.20	23.8
8'	2	0.10	11.8	0.25	29.9
12'	3	0.15	17.7	0.37	44.7

GUIDELINES AND CONTROL SETTINGS

		BTUł	l/ft	Superheat Set			
				Point @ Bulb	Evaporator	Discharge	Discharge Air
Application	Front Sill height	Conventional	Parallel	(°F)	(°F)	Air (°F)	Velocity (FPM)
Beverage/Bulk Produce	2.5" Extended	1231	1200	6 - 8	34	37	210
Beverage/Bulk Produce	5" Extended	1209	1175	6 - 8	34	37	210
Beverage/Bulk Produce	7.5" Extended	1188	1155	6 - 8	34	37	210
Beverage/Bulk Produce	Std. Dairy	1270	1235	6 - 8	34	37	210
Dairy/Deli/Cut Produce	2.5" Extended	1611	1410	6 - 8	28	31	210
Dairy/Deli/Cut Produce	5" Extended	1583	1385	6 - 8	28	31	210
Dairy/Deli/Cut Produce	7.5" Extended	1560	1365	6 - 8	28	31	210
Dairy/Deli/Cut Produce	Std. Dairy	1651	1445	6 - 8	28	31	210

DEFROST CONTROLS

	Defrosts Per	Timed-	Off Defrost
Application	Day	Fail-Safe (Min)	Termination Temp (F)
Beverage/Bulk Produce	2	30	47
Dairy/Deli/Cut Produce	6	40	47

NOTES:

- "---" indicates that the feature is not an option on this case model and/or the data is not available at this time.
- Listed BTUH/ft data represent unlighted shelves. For LED lighting, add 9 BTUH/ft per row of lighted shelving.
- BTUH load increases by 132 BTUH/ft when aftermarket merchandising accessories are utilized.
- Listed evaporator temperature represents unlighted shelves. For lighted shelves and/or aftermarket merchandising accessories, reduce the listed evaporator temperature by 2°F.
- Conventional Discharge Air Control Recommended Settings: Cut-In Temp = Discharge Air + 2°F; Cut-Out Temp = Discharge Air 2°F.
- · Listed discharge air velocity represents the average velocity immediately after defrost.
- Temperature and defrost settings listed above are recommended start-up settings. Final operational settings may need to be adjusted for the store conditions in which the case operates.
- The recommended evaporator temperatures may need to be adjusted based on system setup, store conditions, etc. The minimum recommended evaporator temperature is 4°F below the listed evaporator temperature.
- The published evaporator temperature for zeotropic refrigerants represents the midpoint between dew and bubble points.




ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE



ON5DMHX-NRG 4', 6', 8' & 12' High Narrow Multi-Deck Merchandiser with Synerg-E[™] Beverage / Dairy / Bakery / Cut Produce / Produce



OPTION PAGE NOTES:

- Tag molding materials are PVC, aluminum, or painted aluminum.
- · See Ecoblade tech sheet for additional information.



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE



SHELF TAG MOLDING OPTIONS	PRODUCT STOP OPTIONS (ONLY APPLICABLE ON SLOTTED TM)	SHELF EDGE ENERGY SAVINGS
<u>1.25" STD</u>	<u>3" PLEXI PRODUCT STOPS</u>	ECO BLADE FLAT SHELF
l	3" [7,6 on]	SHELF
SLOTTED	5" PLEXI PRODUCT STOPS	ECO BLADE ANGLED SHELF
I	5" [12.7 cm]	OPTIONAL PRODUCT STOP
ANGLED	WIRE FENCE PRODUCT STOPS	
J ~	3 3/8" [8,7 cm]	
ANGLED SLOTTED		
1%		

OPTION PAGE NOTES:


- Tag molding materials are PVC, aluminum, or painted aluminum.
- See Ecoblade tech sheet for additional information.



COMPONENT ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE





NOTES:

- Ends shown are for general use only. Shape, size, and appearance are subject to change based on engineering configuration.
- Hatched regions represent glass inserts.
- Ends are approximately 1 1/2" thick.
- · Ends add approximately 1" to case height, 1/2" to the back & 1" to the front.




ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE



ON5DMHX-NRG ^{4', 6', 8' & 12'} High Narrow Multi-Deck Merchandiser with Synerg-E[™] Beverage / Dairy / Bakery / Cut Produce / Produce



NOTES:

- * :STUB-UP AREA
- ** :RECOMMENDED STUP-UP CENTERLINE FOR ELECTRICAL AND DRAINS
- ①:AVAILABLE SHELF SIZES: 10", 12", 14", 16", 18" & 20"
- Ends add approximately 1" to case height, 1/2" to the back & 1" to the front.
- · Back panels add approximately 1" to the rear of the case.



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
07-15-21	10	ENDVIEW UPDATE
05-19-21	9	NOTE UPDATE

