
SOLOCHILL

GENERAL NOTES

• "---" indicates the feature is not an option for this model and/or the data is not yet available.



SHIPPING WEIGHT		
Case Weight		
OWZGGQA		







■ COMPONENT

ALL MEASUREMENTS ARE TAKEN PER
ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX
REFRIGERATED DISPLAY CASES FOR SALE IN THE
UNITED STATES MEET OR EXCEED DEPARTMENT
OF EMPENY CASES FOR SALE IN THE OF ENERGY 2017 REQUIREMENTS.

OWZGGQA

Rev. Date	Rev.#	Rev. Title
8-10-20	2	SOLOCHILL V5
3-30-20	1	OPTIONS UPDATE





ELECTRICAL DATA						
		High Effi Far	•	_	ndensate aters	
Case	Fans Per	120 Volt		120	Volts	
Length	Case	Amps	Watts	Amps	Watts	
12'	3	0.18	14.0	2.10	253.0	

DEFROST CONTROLS					
		Elect	ric Defrost		
Defrosts Per	Run Off	Fail Safe	Termination		
Day	Time (Min)	(Min)	Temp (°F)		
3	5	50	45		

NOTES

- "---" indicates that the feature is not an option on this case model and/or the data is not yet available.
- · Listed discharge air velocity represents the average velocity at the peak of defrost.
- · Temperature and defrost settings listed above are recommended start-up settings. Final operational settings may need to be adjusted for the store conditions in which the case operates.



OF ENERGY 2017 REQUIREMENTS.





OWZGGQA

Rev. Date	Rev.#	Rev. Title
8-10-20	2	SOLOCHILL V5
3-30-20	1	OPTIONS UPDATE



OWZGGQA



SOLOCHILL DATA			@95° Condensir	g Temperature
Volts	Phase Frequency		Wire	
208	1 60		3 Wire + Ground	
Case Length	Evaporator Temp (°F)		Discharge Air (°F)	Discharge Air Velocity (FPM)
12'	-22		-15	345

Case	R448A					
Length	Condensing Unit Model	MCA	МОР	Required Capacity	THR (BTUH)	Flow Rate
12'	DA420	36.4	40	6516	10452	3.0







■ COMPONENT


ALL MEASUREMENTS ARE TAKEN PER
ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX
REFRIGERATED DISPLAY CASES FOR SALE IN THE
UNITED STATES MEET OR EXCEED DEPARTMENT
OF ENERGY 2017 REQUIREMENTS.

OWZGGQA

Rev. Date	Rev.#	Rev. Title
8-10-20	2	SOLOCHILL V5
3-30-20	1	OPTIONS UPDATE



SOLOCHILL










ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

OWZGGQA

Rev. Date	Rev.#	Rev. Title
8-10-20	2	SOLOCHILL V5
3-30-20	1	OPTIONS UPDATE







NOTES

- * :STUB-UP AREA
- **: RECOMMENDED STUB-UP CENTERLINE FOR ELECTRICAL AND HUB DRAINS
- · Ends add approximately 1" to case height.







■ COMPONENT

ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

OWZGGQA 4

Rev. Date	Rev.#	Rev. Title
8-10-20	2	SOLOCHILL V5
3-30-20	1	OPTIONS UPDATE

